

Mobil Super DEXRON-VI ATF

Automatic Transmission Fluid

Product Description

Mobil Super DEXRON-VI ATF is a high performance, synthetic blend formulation that meets the stringent requirements of GM's DEXRON-VI specification and provides warranty protection for 2006 and newer GM vehicles. It also provides improved performance in older GM vehicles, wherever DEXRON is specified.

Features and Benefits

Advantages offered by Mobil Super DEXRON-VI ATF over Dexron/Mercon type transmission fluids:

- Extended fluid life
- Improved oxidation and thermal stability
- Optimized frictional properties that provide smooth gear shifting during low temperature operation and help prevent transmission vibration
- Outstanding resistance against sludge and deposit formation
- Improved anti-wear protection which contributes to extended transmission life
- Outstanding low temperature performance

Applications

Mobil Super DEXRON-VI ATF provides warranty protection for 2006 and newer GM vehicles. It also provides improved performance in older GM vehicles, wherever DEXRON is specified.

Due to continual product research and development, the information contained herein is subject to changes without notification. Additional important health and safety information on this product can be found in the Material Safety Data Sheet, which is available online at www.imperialoil.ca/mobil or by contacting Lubricants and Petroleum Specialities, Technical Services, Technical Help Desk: 1-800-268-3183

© 2001 Imperial Oil
© The Mobil logotype and the Pegasus design are registered trademarks of Exxon Mobil Corporation.
™ Trademark of Exxon Mobil Corporation, Imperial Oil, Licensee.



Specifications and Approvals

Mobil Super DEXRON-VI ATF	
General Motors' DEXRON-VI	X

Typical Properties

Mobil Super DEXRON-VI ATF	
Viscosity	
cSt @ 40°C	29.5
cSt @ 100°C	5.83
cP @ -40°C	11,500
Viscosity Index	145
Flash Point, °C	220
Gravity, API	35.76
Color	Red

Precautions

MOBIL SUPER DEXON -VI ATF is manufactured from a blend of high quality synthetic and conventional base stocks, carefully blended with selected additives. As with all petroleum products, good personal hygiene and careful handling should always be practiced. Avoid prolonged contact to skin, splashing into the eyes, ingestion or vapour inhalation. Special care is also recommended in handling used motor oils. A Service Data Sheet entitled "Safe Handling of Used Motor Oils" is available on request from you Imperial Oil Representative. Please refer to our Imperial Oil Material Safety Data Sheet for further information.

Note: This product is not controlled under Canadian WHMIS legislation.

The Mobil logotype, the Pegasus design and Mobil Super are trademarks of Exxon Mobil Corporation, or one of its subsidiaries. DEXRON® and MERCON® are registered trademarks of General Motors and Ford Motor Company, respectively.

8-2008

Due to continual product research and development, the information contained herein is subject to changes without notification. Additional important health and safety information on this product can be found in the Material Safety Data Sheet, which is available online at www.imperialoil.ca/mobil or by contacting Lubricants and Petroleum Specialties, Technical Services, Technical Help Desk: 1-800-268-3183

© 2001 Imperial Oil
® The Mobil logotype and the Pegasus design are registered trademarks of Exxon Mobil Corporation.
™ Trademark of Exxon Mobil Corporation, Imperial Oil, Licensee.

